

Supreme Series



TECHNICAL SPECIFICATION

INPUT	Voltage Range	74VAC~150VAC/140V AC to 285V AC
	Frequency	50 Hz/60Hz +/- 10%
OUTPUT	Power	800 VA
	Voltage (Battery Mode)	110VAC/230V AC
	Frequency (Battery Mode)	50Hz. +/-1%
	Voltage (Mains AVR Mode)	220VAC +/- 5%
	Transfer Time (Typical a.s.)	2 m.s.
	Output Waveform	Modified sine wave
PROTECTION	Surge Protection	Optional
	Input Fuse	Optional
BATTERY	Type	Sealed Lead Acid Maintenance Free
	Number	1 x 12V7.5Ah
	Typical Recharge Time	4 Hours (Upto 90% of full capacity)
	Protection	Deep Discharge Protection
	Back Up Time(at a PC load with 15" monitor)	10~15Minutes
PHYSICAL	Net Weight (kg.)	4.4
	Gross Weight (kg.)	4.7
	Dimensions (LxWxD) (mm)	280x95x140
LED COLOR INDUCATION	Mains Normal (Switch On)	Green (Constant)
	Mains Normal (Switch Off)	Green (Blinks)
	On Batt. Mode	Orange
	Low Battery Pre-alarm	Orange (Blinks)
	Over load/Batt.Low/Batt. Mode Short-Circuit Trip	Red for 10 sec.
	No Load Shut Down	Red Blinks for 10 sec.
	On Battery Mode	Beeps every 30 sec.
ALARMS	Low Battery Pre-alarm	Beeps twice every 3 sec.
	Over load/Batt.Low/Batt. Mode Short-Circuit Trip	Continuous beeping for 10 sec.
ENVIRONMENTAL	Operating Temperature	0-40°C (32-104°F)
	Storage Temperature	0-40°C (32-104°F)
	Humidity	0-95% RH non-condensing
	Noise level	<40dB
PACKING	Giftbox Dimensions (LxWxD) (mm)	327x218x132
	Giftbox pack type	4 in 1
	Carton Dimensions (LxWxD) (mm)	546x339x230

Back panel options



Contact :

UniThai Southern Co., Ltd.

19/1 Moo6 Thepkrasattri Road, Tambon Rasada, Amphur Muang
Phuket 83000 (Thailand)

Tel.076-222770 - 1 Fax.076-222772 www.unithaisouthern.co.th