

Delux Series



INPUT	Voltage Range	74VAC~150VAC/140V AC to 285V AC
	Frequency	50 Hz/60Hz +/- 10%
OUTPUT	Power	1000VA
	Voltage (Battery Mode)	110VAC/230V AC
	Frequency (Battery Mode)	50Hz./+/- 1%
	Voltage (Mains AVR Mode)	198-256V AC
	Transfer Time (Typical a.s.)	3 m.s.
	Output Waveform	Modified sine wave
PROTECTION	Surge Protection	Optional
	Input Fuse	Optional
BATTERY	Type	Sealed Lead Acid Maintenance Free
	Number	One 12V 9AH
	Typical Recharge Time	4 Hours (Upto 90% of full capacity)
	Protection	Deep Discharge Protection
	Back Up Time(at a PC load with 15" monitor)	15~20Minutes
PHYSICAL	Net Weight (kg.)	6.0
	Gross Weight (kg.)	6.4
	Dimensions (LxWxD) (mm)	315x95x146
LED COLOR INDUCATION	Mains Normal (Switch On)	Green (Constant)
	Mains Normal (Switch Off)	Green (Blinks)
	On Batt. Mode	Orange
	Low Battery Pre-alarm	Orange (Blinks)
	Over load/Batt.Low/Batt Mode Short-Circuit Trip	Red for 10 sec.
	No Load Shut Down	Red Blinks for 10 sec.
ALARMS	On Battery Mode	Beeps every 30 sec.
	Low Battery Pre-alarm	Beeps twice every 3 sec.
	Over load/Batt.Low/Batt. Mode Short-Circuit Trip	Continuous beeping for 10 sec.
	Noise level	<40dB
ENVIRONM- ENTAL	Operating Temperature	0-40°C (32-104°F)
	Storage Temperature	0-40°C (32-104°F)
	Humidity	0-95% RH non-condensing
PACKING	Giftbox Dimensions (LxWxD) (mm)	370x133x225
	Giftbox pack type	4 in 1
	Carton Dimensions (LxWxD) (mm)	376x276x463